

BP Lifts

By Barker Products 1310 Miller Road, Greenville, SC 29607




Part # BU19341





- Dependable Smooth Acting 27K Helical Rotary Actuator
- Splined Shafts To Eliminate Arm Movement And Wear
- 50 Degree Dump Angle
- No Grease Points
- EZ Bolt On Kit Standard
- Meets ANSI Z245 Type B Specs
- Lifts All Standard American 2 Bar Carts
- Liftplate Arc Motion Makes Cart Attachment Fast And Easy On Unlevel Highway Conditions
- Double Wide Mounting Plate Available. Increases Hopper Height To Decrease Packing Cycles
- 39 to 43 Inch Mounting Height
- 23 1/8 to 25 1/8 Inch Ground Clearance
- Use on Rear Loaders with or without kick bars
- Limit Hydraulic Input Pressure To 1700PSI



1	P	

BARKER PRODUCTS 1310 MILLER ROAD GREENVILLE, SC 29607

DRAWN BY: R WYMAN 7/26/2021 DATE: MATERIAL: NOTED

DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED MODEL BPHB27-4541
DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL ±1/32
ANGULAR: MACH ±1° BEND ±1°
TVO PLACE DECIMAL ±0.010
THREE PLACE DECIMAL ±0.005

SCALE: 1:8
WEIGHT: 1

HB27-4541

REV 00 SHEET 1 DF 1 160.241




BP LIFTS

By Barker Products
1310 Miller Road, Greenville, SC 29607
Phone:800-349-3149—Fax:707-371-4886
WWW.BPLIFTS.NET



Lift Unit Installation

- 1. Truck must be empty, clean and parked on a level surface before installation is started.
- 2. Remove all bumpers and running boards that will interfere with the location of the lift units. Relocate lower mounted tail lights as needed.
- 3. Measure and mark the centerline of the truck hopper. The centerline of the unit or units should be a minimum of 17" from the hopper centerline.
- 4. Hand valves should be mounted on the side of the hopper at the most convenient height for the operator and clear of the packer controls.
- 5. The top of the unit mounting plate should be tack welded in place at the height recommended on the envelope dimension sheet of the unit. CAUTION: SEE NOTE BELOW PICTURE
- 6. All dimensions should be approved by the customer before final welding.
- 7. If the mounting plate extends more than 2" above the hopper, a brace should be added.



Mounting heights and locations are recommendations only. It is the responsibility of the installer to insure that the customer is satisfied with the height. Barker Products recommends that after the units are tacked in place, try the units with the can or cans the customer uses. The customer should approve your mount before final welding.



BP LIFTS

By Barker Products 1310 Miller Road, Greenville, SC 29607 Phone:800-349-3149—Fax:864-297-1292



BPHB27-193XX SERIES LIFT UNIT WARRANTY

Barker Products warranties each new dump unit to be free of defects in material and workmanship under normal use and service for a period of 1 year or 2000 hours of operation, whichever comes first, from the date of delivery.


This warranty excludes any obligations by BARKER PRODUCTS for the cost of down time. BARKER PRODUCTS will not warranty any dump unit which has been subject to misuse, neglect, alteration, or damaged by an accident.

On any work not performed by BARKER PRODUCTS or it's representitive, the customer will be responsible for freight charges on all parts shipped under warranty. Parts will be invoiced at time of shipment. Defective parts must be returned to BARKER PRODUCTS within 30 days. If the part is determined to be defective the customer will be credited for the original invoice.

Customer warranty labor charges must be approved by BARKER PRODUCTS in advance. If not contacted for approval, BARKER PRODUCTS will not be liable for the warranty labor charge.

Limit hydraulic input pressure to 1700 PSI

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	BWA19015	MAINFRAME SUB ASSY	1
2	BWA19290	LIFT PLATE SUB ASSY	1
3	BWA19280	SLIDE SUB ASSY	1
4	BW18050	SL PIVOT CAP	4
5	BW99108	1/2" SPHERICAL BEARING	4
6	BW18005	SPLINE CAP HB25	2
7	XAD081312	1/2-13 X 1 1/2 FHCS	2
8	XAE081312	1/2-13 X 1 1/2 FLANGED HHCS	10
9	XDH081300	1/2-13 FLANGED NUT	10
10	BW19341	LEFT LIFT ARM	1
11	BW19322	SLIDE LINK	2
12	BW19342	RIGHT LIFT ARM	1
13	XAB101110	5/8-11 X 1 1/4 SHCS	4





DRAWN BY: R WYMAN

2/24/2022 DATE:

MATERIAL:

FRACTIONAL±1/32 ANGULAR: MACH±1° BEND ±1° TWO PLACE DECIMAL ±0.010 THREE PLACE DECIMAL ±0.005 NOTED


HB27-45341 PARTS DWG UNLESS OTHERWISE SPECIFIED: MODEL BPHB27-4541
DIMENSIONS ARE IN INCHES
TOLERANCES:

DRAWING NO

DRAWING NO BU19341 PARTS REV 00

WEIGHT: 162.500 # SHEET 1 OF 1 SCALE: 1:8

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	BW19015	MAINFRAME	1
2	BW18002	O-RING GREASE SEAL	2
3	BW17525	MOUNT PLATE - N	1
4	BW18050	SL PIVOT CAP	4
5	XEB081000	1/2 LOCK WASHER	6
6	XAB101110	5/8-11 X 1 1/4 SHCS	4
7	BV00064	6T X 6S ORIFICE FITTING	1
8	BV00025	116 X 1/8 NPT ORIFICE PLUG	2
9	BR04842	6502-06-06 MJ-FJS 45 DEG	2
10	BR03830	6400-06-06 M TUBE TO O-RING	1
11	BW07140	PLATE STUD	6
12	XDA082000	1/2-20 HEX NUT	6
13	XAE081312	1/2-13 X 1 1/2 FLANGED HHCS	4
14	XDH081300	1/2-13 FLANGED NUT	4
15	BW18300	27K HELICAL ACTUATOR	1
16	XEB101000	5/8 LOCKWASHER	4



TOLERANCES:

FRACTIONAL±1/32 ANGULAR: MACH±1° BEND ±1°

TWO PLACE DECIMAL ±0.010

THREE PLACE DECIMAL ±0.005

DRAWING NO

SCALE: 1:8

BWA19015 PARTS

WEIGHT: 72.623 #

REV

00

SHEET 1 OF 1

BARKER PRODUCTS

1310 MILLER ROAD

GREENVILLE, SC

29607

DRAWN BY: R WYMAN


DATE:

MATERIAL:

2/23/2022

NOTED

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	BW19290	LIFT PLATE	1
2	BW00800	SADDLE	1
3	XEA061000	3/8 LOCKWASHER	9
4	XDA061600	3/8-16 HEX NUT	9
5	BW10675	CAN SUPPORT	2
6	XAD061616	3/8-16 X 2 FSHCS	6
7	BW19110	SLIDE SPACER	2
8	BW19100	SLIDE CAP	2
9	XAA061610	3/8-16 X 1 1/4 HHCS	3





DRAWN BY: R WYMAN

DATE: 2/24/2022 MATERIAL: NOTED DO NOT SCALE
DRAWING


UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL±1/32
ANGULAR: MACH±1°BEND±1°
TWO PLACE DECIMAL ±0.010
THREE PLACE DECIMAL ±0.005

	LIFT PLATE SUB ASSY	
):		

DRAWING NO BWA 19290 REV 00

SCALE: 1:8 WEIGHT: 38.632 # SHEET 1 OF 1

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	BW10230	SLIDE PLATE	1
2	XAD061606	3/8-16 X 3/4 FHSCS	12
3	BW10240	SLIDE SUPPORT	4
4	BW10100	hook shaft	1
5	BW10110	SPRING SHAFT	1
6	BW02125	5/32 X 3/4 SPRING PIN	2
7	BW10120	hook spring	2
8	BW19285	SLIDE DRIVE	2
9	BW10680	LOWER HOOK	1
10	BW19286	SLIDE DRIVE EXTENSION	4
11	BW19287	extension spacer	2
12	XAE061612	3/8-16 X 1 FLANGED HHCS	6
13	XAE081312	1/2-13 X 1 1/2 FLANGED HHCS	4



BARKER PRODUCTS 1310 MILLER ROAD GREENVILLE, SC 29607

DRAWN BY: R WYMAN

2/24/2022 DATE: MATERIAL: NOTED

DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED: BU19X39
DIMENSIONS ARE IN INCHES
TOLERANCES: FRACTIONAL±1/32
ANGULAR: MACH±1° BEND ±1°
TWO PLACE DECIMAL ±0.010
THREE PLACE DECIMAL ±0.005

SLIDE SUB ASSY

SCALE: 1:8

DRAWING NO REV BWA19280 00

WEIGHT: 32.629 #

SHEET 1 OF 1